

MINIBREW

YOU CAN'T BUY WHAT YOU CAN BREW

ASSEMBLY INSTRUCTIONS

THE EZ SEAL

STAINLESS STEEL WELD-LESS BULK HEAD FITTING

THREE PARTS TO THE EZ SEAL BULKHEAD ARE AS FOLLOWS:

1. THE NUT
2. THE RED FOOD GRADE WASHERS
3. THE HOLLOW DOUBLE THREADED BOLT

The nut on the outside of the bolt turns left to tighten. The threads inside the bolt are standard right hand threads. One Red Food Grade washer is placed on the inside the of the tank. Push the bolt and washer through the hole from inside the tank. Place the second Red Washer on the bolt. Turn the nut counter-clock wise onto the bolt.

The nut at the end of the bolt consists of two flat areas for an adjustable wrench. Use this to tighten/loosen the nut and nipple that connects to the valve.

The nut at the end of the bolt consists of two flat areas for an adjustable wrench. Use this to tighten/loosen the nut and nipple that connects to the valve.

For larger tanks where access is difficult, use a length of string, rope or the like to thread the Nut down to the hole. The Nut will slide through the hole. With a finger, hold the Nut in place and place the Second Washer on the Nut. Keep your finger in the Nut while you start the Bolt portion of the EZ Seal. Tighten as needed.

To attach a Ball Valve, thread the Hex Nipple into the outside end into the **EZ Seal Nut**. From there, thread the Ball Valve into the outside portion of the Hex Nipple. Now tighten, using an adjustable or crescent wrench.

Multiple washers can be used on the **EZ Seal**, both inside and outside the tank.

MINIBREW

YOU CAN'T BUY WHAT YOU CAN BREW

You can attach an **EZ Seal**[®] to anything where you need a Sealed Threaded Fitting, by drilling the proper size hole. Drill a **1 1/8**, **1 3/8** and **1 5/8** inch hole respectively, for our **1/2**, **3/4** and **1** inch **EZ Seal**[®] **Bulk Head Fittings**.

